

Fine Control Valve

FCV



Features:

- 1/4" BSPP Connection fits directly into pipework
- Fits in any orientation
- Choice of low, medium or high flow control
- Ideal for use with NGXI, LGXI and GU flowmeters
- Brass or Stainless Steel Options



Description:

A selection of fine control needle valves suitable for gradual opening and closing of gas or liquid flows. Suitable for use with all Platon glass Tube VA flowmeters, the standard FCV is rated at up to 25 bar line pressure. As with all control valves the FCV is not designed for total leak free shut off.

Valve Body	Brass or Stainless Steel
Valve Needle	316 Stainless Steel
Seals	Nitrile with Brass Viton with Stainless Steel
Connections	1/4" BSPP Female thread
Max Operating Pressure	25 bar, higher to special order
Max Operating Temp	80°C

*CVA Adaptors available for LGXI/NGXI and GU series Flowmeters

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Roxspur Measurement & Control
2 Downgate Drive, Sheffield, South Yorkshire, S4 8BT, UK | Ph: +44 (0) 114-244-2521
www.ttelectronics.com | RoxspurSales@ttelectronics.com