INTERCHANGEABLE WALL PLUG POWER SUPPLY 24VDC 40WATT

STONTRONICS: T5778ST

Features:

- Interchangeable AC Heads
- 1 Year Warranty
- Level VI Efficiency
- Worldwide Approvals
- Safety approved to: UL62368-1, EN62368-1, UKCA62368-1 (Pending)

Electronics Solve the second second

Description:

Our range of 40 Watt Interchangeable wall plug power supplies provide 40 Watts of continuous power with the flexibility of worldwide usage as they are supplied with UK, Euro, USA AC Heads, all Efficiency Level VI and carry worldwide safety approvals.

| Specification | |
|--------------------------|---|
| Part Code | T5778ST |
| Input Voltage Range | 90-264 Vac |
| Input Frequency Range | 47-63Hz |
| Input Current Rated | 1.0A Max |
| Input AC Heads | UK, Euro, USA |
| Output Voltage Rating | +24V |
| Output Current Range | 1.7A Max |
| Output Min Current | 0A Max |
| Output Connection Type | 2.1x5.5x12mm centre positive – Straight |
| Total Output Regulation | +/- 5% |
| Line and Load Regulation | +/- 5% |
| Ripple & Noise | <240mVp-p |
| Efficiency | 87.62% Min |
| Over Voltage Protection | 30V Max |
| Over Load Protection | ≤2.6A Output Load |
| Operating Temperature | 0°C to +40°C |
| Storage Temperature | -20°C to +70°C |
| Operating Humidity | 20% to 80% |
| Storage Humidity | 10% to 90% |
| Hi-Pot | 3000VAC 10mA 1min |
| Leakage Current | <0.25mA |
| Safety Standard | UL/CUL,EN,GS,CE(LVD),RCM,(UKCA pending) |
| EMI Standard | meet FCC class B , CE ,VCCI – II |
| MTBF | 50K Hours |
| Size mm max. | 90(L) x 38(W) x 59.4(H) mm |
| Weight | 200 g |

INTERCHANGEABLE WALL PLUG POWER SUPPLY 24VDC 40WATT



STONTRONICS: T5778ST

Diagrams



