## INTERCHANGEABLE WALL PLUG POWER SUPPLY 24VDC 24WATT



STONTRONICS: T5788ST

#### **Features:**

- Interchangeable AC Heads
- 1 Year Warranty
- Level VI Efficiency
- Worldwide Approvals



### **Description:**

Our range of 24 Watt Interchangeable wall plug power supplies provide 24 Watts of continuous power with the flexibility of worldwide usage as they are supplied with UK, Euro, USA & Auz AC Heads, all Efficiency Level VI and carry worldwide safety approvals.

Specification	
Part Code	T5788ST
Input Voltage Range	90-264 Vac
Input Frequency Range	47-63Hz
Input Current Rated	0.8A Max
Input AC Heads	UK, Euro, USA & Auz
Output Voltage Rating	+24V
Output Current Range	1.0A
Output Min Current	0.0A
Output Connection Type	2.1x5.5x12mm centre positive – Straight
Total Output Regulation	±5%
Line and Load Regulation	±2%
Ripple & Noise	200mVp-p
Efficiency	86.2%Min
Over Voltage Protection	Removal of an output overload shall provide automatic recovery for the output voltage.
Over Load Protection	Removal of an output overload shall provide automatic recovery for the output voltage.
Operating Temperature	0°C to +40°C
Storage Temperature	-20°C to +70°C
Operating Humidity	10% to 95%
Storage Humidity	10% to 95%
Hi-Pot	3000VAC 4mA 1min
Safety Standard	CE, FCC, C-Tick, UL, TUV, TUV GS,
EMI Standard	FCC PART 15 Class B AS/NZS CISPR 22:2009 Class B EN55022:2010/AC:2011 EN61000-3-2:2006/A2:2009 EN61000-3-3:2008 EN55024:2010/AC:2011 IEC61000-4-2:2008 IEC61000-4-3:2006/A1:2007/A2:2010 IEC61000-4-4:2012 IEC61000-4-5:2005 IEC61000-4-6:2008 IEC61000-4-8:2009 IEC61000-4-11:2004
MTBF	50K Hours
Size mm max.	79.1(L) x 46.2(W) x 37.1(H)
Weight	250 g

### **STONTRONICS**

# INTERCHANGEABLE WALL PLUG POWER SUPPLY 24VDC 24WATT



STONTRONICS: T5788ST

## **Diagrams**

