# EXTERNAL DESKTOP POWER SUPPLY 12VDC 18WATT



### STONTRONICS: T5890ST

#### **Features:**

- Universal Input
- IEC-320-C14 Input Connector
- 3 Year Warranty
- Efficiency Level VI
- Safety approved to: UL,CUL,FCC,GS,CE,RCM UL62638-1, EN62638-1, UKCA62638-1 (Pending)



#### **Description:**

Our Range of 18 Watt AC/DC switch mode power supplies provide 18 Watts of continuous output power in a high quality compact enclosure suitable for many general power applications.

Specification	
Part Number	T5890ST
Input Voltage Range	90 → 264 Vac
Input Frequency Range	47 → 63Hz
Input Connector	IEC 320-C14
Input Current Rated	500mA Rms Max
Inrush Current	50A Max. at 115VAC cold start
	100A Max. at 230VAC cold start
Leakage Current	<3.5mA
Efficiency	85% Min
Input Power (Output: No Load)	<0.1W (CEC & DOE LEVEL VI Compliant)
Output Voltage Rating	12 VDC
Output Current Range	1.5A
Output Min Current	0A
Output Connection Type	2.1 x 5.5 x 12 mm Centre Positive - Right Angle
Line and Load Regulation	+/-5%
Over Voltage Protection	Protection zener
Over Load Protection	<2.5A output load
Short Circuit Protection	Output shut down auto recover
Ripple Voltage	150 mV (p-p) (100V-240V AC Input )
Hi-Pot	1500Vac or 2121VDC 10mA 1 min
Safety Approved	UL,CUL,EN,FCC,GS,RCM,CE,(UKCA pending)
EMI Standard	FCC Class B, CE
Operating Temperature Range	0°C → +40 °C
Storage Temperature	-10°C → +70°C
Operating Humidity	20% to 80%
Storage Humidity	10% to 90%
Dimensions	80.6(L) x 50(W) x 31(H) mm
Product Weight	130 g
Regulator Type	Switched Mode Power Supply

# EXTERNAL DESKTOP POWER SUPPLY 12VDC 18WATT



STONTRONICS: T5890ST

## **Diagrams** 50±1-0 1530±100 31±3 2.8~4.0mm 50±10 L02 48B 70±10 Ø5.5±0.1 Ferrite core with one turns wire S&T 12X20X7.3 Ø2.1±0.1 ( Tuning fork cannelure entire insulation type

### **STONTRONICS**