

# MEDICAL WALL MOUNT INTERCHANGEABLE BLADE POWER SUPPLY 24VDC 18 WATT



STONTRONICS: T6393ST



## Features:

- Interchangeable AC Heads
- 1 Year Warranty
- Level VI Efficiency
- Worldwide Approvals

## Description:

Our range of 18 Watt Medical Interchangeable wall plug power supplies provide 18 Watts of continuous power with the flexibility of worldwide usage as they are supplied with UK, Euro, USA & Auz AC Heads , all Efficiency Level VI and carry worldwide safety approvals.

Specification	
Part Code	T6393ST
Input Voltage Range	90-264 Vac
Input Frequency Range	47-63Hz
Input Current Rated	0.5A Max
Input AC Heads	UK, Euro, USA & Auz
Output Voltage Rating	+24V
Output Current Range	0.75A
Output Min Current	0A
Output Connection Type	2.1x5.5x12mm centre positive – Straight
Total Output Regulation	+/- 5%
Line and Load Regulation	+/- 5%
Ripple & Noise	200mVp-p
Efficiency	85.45% Min.
Over Voltage Protection	24.0VDC Maximum
Over Load Protection	The power supply shall be normal operated automatically when the over current protection is removed.
Operating Temperature	0°C to +40°C
Storage Temperature	-20°C to +60°C
Operating Humidity	10% to 90%
Storage Humidity	5% to 95%
Hi-Pot	5656VAC 10mA 1min
Leakage Current	0.1mA max
Safety Standard	CB, UL, TUV, RCM
EMI Standard	Meets CE(EN55022)
MTBF	50K Hours
Size mm max.	88(L) x 30(W) x 57(H)
Weight	170 g

## STONTRONICS

TT Electronics IoT Solutions Ltd

Tofts Farm East, Brenda Road, Hartlepool, TS25 2BQ, UK

t: +44 (0) 1429 852 500

### General Note


TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

# MEDICAL WALL MOUNT INTERCHANGEABLE BLADE POWER SUPPLY 24VDC 18 WATT



STONTRONICS: T6393ST

## Diagrams



General Note  
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.